

PLATINA GOLD - 120x240cm 09mm - mayceramica.com

| | |
|------------------|-----------------|
| Color | Gold, Off White |
| Size | 120x240cm 09mm |
| Material | Porcelain |
| Finishing | Glossy |

PLATINA GOLD | 120x240cm | 09mm | Glossy Finish Platina Gold brings a lavish appeal with its **soft white surface** adorned by elegant **golden veining**, offering a perfect balance of subtlety and luxury. The **glossy finish** enhances its radiant texture, making it an ideal selection for **premium interiors, luxury flooring**, and **feature walls** that aim to exude warmth, elegance, and timeless charm.

CHARACTERISTIC
STANDARD AS PER ISO-13006/EN14411 GROUP BIA
MAYYAS VALUE
TEST METHOD
REGULATORY PROPERTIES

| | | | |
|------------------------------|-------------|-----------|---------------|
| Deviation in Length & Width: | ± 0.5 % | ± 0.2 % | ISO- 10545-2 |
| Deviation in Thickness: | ± 5.0 % | ± 0.5 % | ISO- 10545-2 |
| Straightness in side: | ± 0.5 % | ± 0.2 % | ISO- 10545-2 |
| Rectangularity: | ± 0.5 % | ± 0.2 % | ISO- 10545-2 |
| Surface flatness: | ± 0.5 % | ± 0.2 % | ISO- 10545-2 |
| Color difference: | Unaltered | No change | ISO- 10545-16 |
| Glossiness: | As per mfg. | Min 90 % | GLOSSOMETER |

STRUCTURAL PROPERTIES

| | | | |
|-------------------|------------|-------------|--------------|
| Water absorption: | < 0.50% | < 0.05 % | ISO- 10545-3 |
| Apparent density: | > 2.0 g/cc | > 2.10 g/cc | DIN 51082 |

MASSIVE MECHANICAL PROPERTIES

| | | | |
|---------------------|---------------------------|---------------------------|--------------|
| Modulus of rupture: | Min. 35 N/mm ² | Min. 40 N/mm ² | ISO- 10545-4 |
| Breaking strength: | Min. 1300 N | Min. 2000 N | ISO- 10545-4 |
| Impact resistance: | As per mfg. | Min. 0.55 | ISO- 10545-5 |

SURFACE MECHANICAL PROPERTIES

| | | | |
|------------------------------|-------------|--------------|--------------|
| Surface abrasion resistance: | As per mfg. | Min. Class 3 | ISO- 10545-7 |
| MOH's hardness: | As per mfg. | Min. Class 4 | EN 101 |

THERMO HYGROMETRIC PROPERTIES

| | | | |
|---------------------------|----------------------------|----------------------------|---------------|
| Frost resistance: | No damage | No damage | ISO- 10545-12 |
| Thermal shock resistance: | No damage | No damage | ISO- 10545-9 |
| Moisture expansion: | Nil | Nil | ISO- 10545-10 |
| Thermal expansion (COE): | Max 9.0 x 10 ⁻⁶ | Max 6.5 x 10 ⁻⁶ | ISO- 10545-8 |
| Crazing resistance: | As per mfg. | Min. 10 cycle | ISO- 10545-11 |

CHEMICAL PROPERTIES

| | | | |
|----------------------|-----------|-----------|---------------|
| Chemical resistance: | No damage | No damage | ISO- 10545-13 |
| Stain resistance: | Resistant | Resistant | ISO- 10545-14 |

SAFTEY PROPERTIES

| | | | |
|---|-------------|------------------------|---------------|
| Slip resistance: | As per mfg. | > 0.40 | ISO- 10545-17 |
| Fire resistance: | As per mfg. | Fireproof | N. A |
| Lead & Cadmium given off by glazed tiles: | As per mfg. | Does not yield Pb & Cd | ISO- 10545-15 |

SIZE
THICKNESS
TILE / BOX
COVERAGE AREA / BOX

| | | | |
|------------|------|-----|------------|
| 120X240cm: | 09mm | 1PC | 2.88 Sq. M |
|------------|------|-----|------------|