

**Calacatta Borghini - 120x320cm 12mm - mayceramica.com**



<b>Color</b>	Grey, White
<b>Size</b>	120x320cm 12mm
<b>Material</b>	Porcelain
<b>Finishing</b>	Glossy

**CHARACTERISTIC**
**STANDARD AS PER ISO-13006/EN14411 GROUP BIA**
**MAYYAS VALUE**
**TEST METHOD**
**REGULATORY PROPERTIES**

Deviation in Length & Width:	± 0.3 %	± 0.10 %	ISO- 10545-2
Deviation in Thickness:	± 5.0 %	± 5.00 %	ISO- 10545-2
Straightness in side:	± 0.3 %	± 0.10 %	ISO- 10545-2
Rectangularity:	± 0.3 %	± 0.10 %	ISO- 10545-2
Surface flatness Central curvature:	± 0.4 %	± 0.50 %	ISO- 10545-2
Surface flatness Edge curvature:	± 0.4 %	± 0.50 %	ISO- 10545-2
Surface quality:	> 95% defects free	> 95% defects free	ISO- 10545-2
Color difference:	E < 1.00	E < 0.30	ISO- 10545-16
Glossiness (With polished):	As per mfg.	> 90 degree	GLOSSOMETER
Glossiness (Without polished):	As per mfg.	3 < Gloss < 7	GLOSSOMETER
Glossiness (Satin):	As per mfg.	7 < Gloss < 18	GLOSSOMETER

**STRUCTURAL PROPERTIES**

Water absorption:	< 0.50%	< 0.060 %	ISO- 10545-3
Apparent density:	As per mfg.	> Min 2.28 g/cc	ISO- 10545-3

**MASSIVE MECHANICAL PROPERTIES**

Modulus of rupture:	Min. 35 N/mm <sup>2</sup>	Min. 42 N/mm <sup>2</sup>	ISO- 10545-4
Breaking strength < 7.5:	Min. 700 N	Min. 700 N	ISO- 10545-4
Impact resistance >7.5:	Min. 1300 N	Min. 1800 N	ISO- 10545-5

**SURFACE MECHANICAL PROPERTIES**

Surface abrasion resistance- Glossy:	As per mfg.	Min. Class 4	ISO- 10545-7
Surface abrasion resistance- Matt:	As per mfg.	Min. Class 6	ISO- 10545-7
MOH's hardness:	As per mfg.	Min. 4	BS EN 15771

**THERMO HYGROMETRIC PROPERTIES**

Frost resistance:	As per mfg.	Frost proof	ISO- 10545-12
Thermal shock resistance:	Min. 10 cycle	Min. 10 cycle	ISO- 10545-9
Moisture expansion:	Max 0.06	Max 0.02	ISO- 10545-10
Thermal expansion (COE):	As per mfg.	Max 6.0 x 10 <sup>-6</sup>	ISO- 10545-8
Crazing resistance:	As per mfg.	Min. 06 cycle	ISO- 10545-11

**CHEMICAL PROPERTIES**

Chemical resistance:	Min. Class 3	Min. Class 4	ISO- 10545-14
Stain resistance:	Min. Class GB	Min. Class GA	ISO- 10545-13

**SAFETY PROPERTIES**

Slip resistance:	As per mfg.	> 0.40	ISO- 10545-17
Fire resistance:	As per mfg.	Fireproof	N. A
Lead & Cadmium given off by glazed tiles:	As per mfg.	Does not yield Pb & Cd	ISO- 10545-15

**SIZE**
**THICKNESS**
**TILE / BOX**
**COVERAGE AREA / BOX**

120X320cm:	12mm	1PC	3.84 Sq. M
------------	------	-----	------------