


**Brio Bianco - 60X120CM 09MM - mayceramica.com**



**Color** Grey

**Size** 60X120CM 09MM

**Material** Porcelain

**Finishing** Matt



**CHARACTERISTIC**
**STANDARD AS PER ISO-13006/EN14411 GROUP BIA**
**MAYYAS VALUE**
**TEST METHOD**
**REGULATORY PROPERTIES**

Deviation in Length & Width:	± 0.5 %	± 0.1 %	ISO- 10545-2
Deviation in Thickness:	± 5.0 %	± 4.0 %	ISO- 10545-2
Straightness in side:	± 0.5 %	± 0.1 %	ISO- 10545-2
Rectangularity:	± 0.5 %	± 0.1 %	ISO- 10545-2
Surface flatness:	± 0.5 %	± 0.2 %	ISO- 10545-2
Color difference:	Unaltered	No change	ISO- 10545-16
Glossiness:	As per mfg.	Min 90 %	GLOSSOMETER

**STRUCTURAL PROPERTIES**

Water absorption:	< 0.50%	< 0.05 %	ISO- 10545-3
Apparent density:	> 2.0 g/cc	> 2.10 g/cc	DIN 51082

**MASSIVE MECHANICAL PROPERTIES**

Modulus of rupture:	Min. 35 N/mm <sup>2</sup>	Min. 40 N/mm <sup>2</sup>	ISO- 10545-4
Breaking strength:	Min. 1300 N	Min. 2000 N	ISO- 10545-4
Impact resistance:	As per mfg.	Min. 0.55	ISO- 10545-5

**SURFACE MECHANICAL PROPERTIES**

Surface abrasion resistance:	As per mfg.	Min. Class 3	ISO- 10545-7
MOH's hardness:	As per mfg.	Min. Class 4	EN 101

**THERMO HYGROMETRIC PROPERTIES**

Frost resistance:	No damage	No damage	ISO- 10545-12
Thermal shock resistance:	No damage	No damage	ISO- 10545-9
Moisture expansion:	Nil	Nil	ISO- 10545-10
Thermal expansion (COE):	Max 9.0 x 10 <sup>-6</sup>	Max 6.5 x 10 <sup>-6</sup>	ISO- 10545-8
Crazing resistance:	As per mfg.	Min. 10 cycle	ISO- 10545-11

**CHEMICAL PROPERTIES**

Chemical resistance:	No damage	No damage	ISO- 10545-13
Stain resistance:	Resistant	Resistant	ISO- 10545-14

**SAFTEY PROPERTIES**

Slip resistance:	As per mfg.	> 0.40	ISO- 10545-17
Fire resistance:	As per mfg.	Fireproof	N. A
Lead & Cadmium given off by glazed tiles:	As per mfg.	Does not yield Pb & Cd	ISO- 10545-15

**SIZE**
**THICKNESS**
**TILE / BOX**
**COVERAGE AREA / BOX**

60x120cm:	09mm	2 Pcs	1.44 Sq. M
-----------	------	-------	------------